



June 2009

Perimeter Plus™ Blown-in-Blanket® System

Description

Knauf Insulation Perimeter Plus™ is an unbonded, virgin glass wool blowing insulation with high thermal resistance characteristics for timber frame construction.

Application

Density (kg/m ³)	Angle range (°)	Thermal conductivity (W/mK)	Application
12.0	0 - 15	0.042	Open Loft
19.0	0 - 25	0.038	Enclosed rafter spaces
23.0	0 - 90	0.036	Enclosed rafter spaces and timber frame stud walls
26.0	0 - 90	0.034	
30.0	0 - 90	0.033	

Thermal resistance values for 26kg/m³

Thickness (mm)	Thermal resistance (m ² K/W)	Maximum coverage per bag (m ²) contents of this bag should not cover more than:
90	2.60	6.20
140	4.10	3.98
200	5.85	2.79
300	8.80	1.86

All dimensions are nominal
Bag net weight - Nominal 14.5kg

Performance

Thermal

Perimeter Plus™ has a range of thermal conductivities between 0.033 - 0.042W/mK depending on the density required in the application.

Fire

Perimeter Plus™ is classified as Euroclass A1 to EN ISO 13501-1

Acoustic performance

Perimeter Plus™ has excellent sound absorption characteristics.

Benefits

- Ultra high energy saving
- Quick and clean to install
- Made using recycled glass bottles
- Installed from inside the house
- Fills all voids
- Non-combustible
- High sound absorption

Perimeter Plus™

Blow-in-Blanket® System (BIBS) is a patented process consisting of glass mineral wool loose fill blown in behind a special netting material for timber frame construction. Perimeter Plus™ Blowing Insulation is used in both new and existing structures as a Blow-In-Blanket System for closed cavity applications in which ventilation is not required.

Features and benefits

Excellent thermal properties, fills all gaps and voids, creating a thermal barrier against outside air thereby improving temperature control.

Environmental

Perimeter Plus™ conserves energy and therefore assists in reducing demand for fuels for the heating and air-conditioning of buildings. As a result, they reduce the emissions of the major greenhouse gas, CO₂. The energy and CO₂ emissions saved by the products in use vastly outweigh those generated in their manufacture. **Perimeter Plus™ has a low impact on the environment and is classified as Zero ODP and Zero GWP.**

Thermal performance

The stated thermal conductivity is provided by installing in accordance with the manufacturer's instructions.

Vapour resistance – resistivity

Perimeter Plus™ offers negligible resistance to the passage of water vapour and has a vapour resistivity of 7.00 MN.s/g.m.

Noise reduction

Improves sound insulation performance of construction element into which it is installed.

Non-corrosive

Will not accelerate the corrosion of aluminum, steel or copper.

Resists microbial growth

Does not promote the growth of fungi or bacteria and will not rot or sustain vermin, rodents or insects.

Poly bag packaging

Excellent protection from on site dust and moisture, unitised packaging eases movement in the warehouse and reduces storage space.

Speed of installation

Saves installation time by minimising the steps needed to fully insulate tight corners and hard to reach areas



Knauf Insulation Pty Ltd

Knauf Insulation Pty Ltd
Unit 2, 39 Devlan Street
Mansfield QLD 4122

Customer Service (sales)

Tel: +61 7 3343 1989
Fax: +61 7 3343 1898
Email: sales@au.knaufinsulation.com

Technical Support

Email: tech@au.knaufinsulation.com

www.knaufinsulation.com.au